


### SPECIFICATIONS

Current Rating: 4A AC,DC  
 Voltage Rating: 125V AC,DC  
 Temperature Range:  $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$   
 Contact Resistance: 10m $\Omega$  Max.  
 Insulation Resistance: 1000M $\Omega$  Min.  
 Withstanding Voltage: 1000V AC/minute  
 Material: Nylon 66,UL94V-0  
 Color: Natural(White)

### Ordering Information & Dimensions

PART NO.	Dimensions		
	A	B	C
A2013H-02P	2.00	6.00	4.80
A2013H-03P	4.00	8.00	6.80
A2013H-04P	6.00	10.00	8.80
A2013H-05P	8.00	12.00	10.80
A2013H-06P	10.00	14.00	12.80
A2013H-07P	12.00	16.00	14.80
A2013H-08P	14.00	18.00	16.80
A2013H-09P	16.00	20.00	18.80
A2013H-10P	18.00	22.00	20.80
A2013H-11P	20.00	24.00	22.80
A2013H-12P	22.00	26.00	24.80
A2013H-13P	24.00	28.00	26.80
A2013H-14P	26.00	30.00	28.80
A2013H-15P	28.00	32.00	30.80

				JOINT TECH ELECTRONIC IND. CO., LTD. JOY DAY INDUSTRIAL CO., LTD.	
		UNIT	SCALE	SHEET	TITLE:
		mm		1 of 1	<b>2.00mm PITCH HOUSING</b>
		DRAWN BY 董正一 2001.02.01	APPROVED BY 董正一 2001.02.01		
B2	REVISE	2006.05.24	GENERAL TOLERANCE		
B1	REVISE	2006.02.18	X. X $\pm$ 0.25	ANGLE $\pm$	
B0	NEW RELEASE	2006.01.07	X. XX $\pm$ 0.15	DRAW NO. : A2013H-XP	
REV.	DESCRIPTION	DATE	X. XXX $\pm$ 0.05		